

## ORDINANCE 671

### AN ORDINANCE PROVIDING FOR THE ADOPTION OF THE 2018 INTERNATIONAL EXISTING BUILDING CODE AND AMENDMENTS AND ADDITIONS THERETO; AND FOR THE REPEAL OF ALL ORDINANCES AND RESOLUTIONS IN CONFLICT THEREWITH.

**BE IT ORDAINED BY THE CITY OF HARTFORD, SOUTH DAKOTA:**

**SECTION 9.1301. Adoption International Existing Building Code 2018.**

The International Existing Building Code, 2018 edition, including Resource A, Guidelines on Fire Ratings of Archaic Materials and Assemblies, as published by the International Code Council Inc., and amendments and additions thereto as provided in this ordinance are hereby adopted as the Existing Building Code by the City of Hartford as an alternate for regulating and governing the repair, alteration, change of occupancy, addition, and relocation of existing buildings, including historic buildings, as herein provided and provides for the issuance of permits and collection of fees therefore. The alternate minimum building standards in the 2018 edition of the International Existing Building Code and amendments thereto shall be applied to any building permit issued after July 3, 2019. The adoption of the International Existing Building Code, 2018 edition will become effective July 3, 2019. A printed copy of such code and additions and amendments thereto is on file with the City of Hartford.

**SECTION 9.1302. Amendments, additions and deletions to the 2018 International Existing Building Code.**

The following sections and subsections of building code adopted in this subchapter shall be amended, added, or deleted as follows. All other sections or subsections of the 2018 International Existing Building Code shall remain the same.

**101.1 Title.** These regulations shall be known as the Existing Building Code of the City of Hartford, South Dakota hereinafter referred to as “this code.”

**103.1 Enforcement agency.** The City of Hartford shall be the enforcement agency and the individual in charge thereof shall be known as the zoning administrator.

**103.2 Appointment.** This section not adopted by the City of Hartford.

**104.8 Liability.** The zoning administrator, building official, member of the board of appeals, or employee charged with the enforcement of this code, while acting for the jurisdiction in good faith and without malice in the discharge of the duties required by this code or other pertinent law or ordinance shall not thereby be rendered liable personally and is hereby relieved from personal liability for any damage accruing to persons or property as a result of an act or by reason of an act or omission in the discharge of official duties. Any suit brought against the

zoning administrator, building official, officer or employee because of such act or omission performed by the zoning administrator, building official, officer or employee in the lawful discharge of duties and enforcement of any provision of such codes or other pertinent laws or ordinances implemented through the enforcement of this code or enforced by the code enforcement agency shall be afforded all the protection provided by the City's liability insurance and any immunities and defenses provided by other applicable state and federal laws. The zoning administrator, building official or any subordinate shall not be liable for cost in any action, suit or proceeding that is instituted in pursuance of the provisions of this code.

This code shall not be construed to relieve from or lessen the responsibility of any person owning, operating or controlling any building or structure for any damages to persons or property caused by defects, nor shall the county, its officers, and employees be held as assuming any such liability by reason of the inspections authorized by this code or any permits or certificates issued under this code.

**104.11 Alternative materials, design and methods of construction, and equipment.** The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code, provided that any such alternative has been approved. An alternative material, design, or method of construction shall be approved where the code official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method, or work offered is, for the purpose intended, not less than the equivalent of that prescribed in this code in quality, strength, effectiveness, fire resistance, durability and safety.

**105.1 Required.** Any owner or owner's authorized agent who intends to repair, add to, alter, relocate demolish, or change the occupancy of a building or to repair, install, add, alter, remove, convert, or replace any electrical, gas, mechanical, or plumbing system, the installation of which is regulated by this code unless a separate permit for each building or structure has first been obtained from the zoning administrator or designate. Permits for minor work may be exempted by the zoning administrator or designate.

**105.1.1 Annual permit.** Not adopted by the city.

**105.1.2 Annual permit record.** Not adopted by the City.

**107.1 General.** The zoning administrator is authorized to issue a permit for temporary uses. Such permits shall be limited as to time of service but shall not be permitted for more than 365 days. Extensions beyond 365 days are not allowed. Structures used as a temporary business office shall be provided with an accessible route that meets accessibility requirements of this code.

**108.7 Delinquent accounts.** The City of Hartford may refuse to issue permits or conduct inspections for any person or business whose account is delinquent.

**109.3.1 Footing inspection.** Footing inspections shall be made after excavations for footings are complete and any required reinforcing steel is in place. If an inspection is required for concrete foundations, any required forms shall be in place prior to inspection. Materials for the foundation shall be on the job, except where concrete is ready mixed in accordance with ASTM C 94, the concrete need not be on the job.

**110.1 Change of Occupancy.** No building shall be used or occupied while undergoing a change in occupancy, and no change in the existing occupancy classification of a building or portion thereof shall be made until the building official has completed a final inspection and all construction and code requirements have been met to the building official's satisfaction and a certificate of occupancy has been issued. Issuance of a certificate of occupancy shall not be construed as an approval of a violation of the provisions of this code or of other ordinances of the jurisdiction.

**110.2 Certificate issued.** After the building official inspects the building and finds no violations of the provisions of this code or other laws that are enforced by the City, the building official shall issue a certificate of occupancy that shall contain the following:

1. The building permit number
2. The address of the structure.
3. The legal address.
4. The date of issuance.
5. The name of the building official.

**112.1 General.** In order to hear and decide appeals of orders, decisions or determinations made by the zoning administrator, building official or employee relative to the application and interpretation of this code, there shall be and is hereby created a Board of Appeals consisting of the members of the City of Hartford Planning and Zoning Board.

**112.2 Limitations on authority.** An application for appeal shall be based on a claim that the true intent of this code or the rules legally adopted there under have been incorrectly interpreted, the provisions of this code do not fully apply, or an equally good or better form of construction is proposed. The board shall have no authority relative to the administrative provisions of this code nor shall the board be empowered to waive requirements of this code.

**113.3 Prosecution of violation.** If the notice of violation is not complied with promptly, the building official is authorized to request the legal counsel of the jurisdiction to deem the violation as a strict liability offense and institute the appropriate proceeding at law or in equity to restrain, correct, or abate such violation or to require the removal or termination of the unlawful occupancy of the building or structure in violation of the provisions of this code or of the order or direction made pursuant thereto.

**SECTION 202-GENERAL DEFINITIONS.** Add the following definition.

**Strict Liability Offense.** An offense, in which the prosecution in a legal proceeding, is not required to prove criminal intent as a part of its case. It is enough to prove that the defendant either did an act which was prohibited, or failed to do an act which the defendant was legally required to do.

**302.3 Additional codes.** Alterations, repairs, additions, and changes of occupancy to, or relocation of, existing buildings and structures shall comply with the provisions for alterations, repairs, additions and changes of occupancy or relocation, respectively, in this code and the International Energy Conservation Code, International Fire Code, International Fuel Gas Code, International Mechanical Code, Uniform Plumbing Code, International Property Maintenance Code, International Residential Code, and NFPA 70 as adopted by the State of South Dakota. Where provisions of the other codes conflict with provisions of this code, the provisions of this code shall take precedence.

**406.1 Material.** Existing electrical wiring and equipment undergoing repair shall be allowed to be repaired or replaced with like material. Minor additions, alterations, and repairs to existing electrical systems or equipment may be installed in accordance with the law in effect at the time the original installation was made, when approved by the electrical inspector.

**406.1.4 Group B and Group I-2 receptacles.** Receptacles in patient bed locations of Group B medical offices and ambulatory health care facilities, and Group I-2 that are not “hospital grade” shall be replaced with “hospital grade” receptacles, as required by NFPA 99 and Article 517 of NFPA 70.

**406.1.6 New electrical service entrances in existing single-family and multiple family dwellings.** When adding a new service entrance with increased amperage, the existing electrical system shall, at a minimum, comply with the following:

- (1) *Kitchens.* Each kitchen shall have a minimum of one 20-ampere circuit serving a countertop receptacle and a grounded receptacle serving a refrigerator.
- (2) *Overcurrent device location.* Each occupant shall have access to his branch circuit overcurrent devices without going outdoors or through another occupancy.
- (3) *Habitable areas.* All habitable areas, other than closets, kitchens, basements, garages, hallways, laundry areas, utility areas, storage areas, and bathrooms, shall have a minimum of two duplex receptacle outlets, or one duplex receptacle outlet and one ceiling or wall-type lighting outlet.
- (4) *Minimum lighting outlets.* At least one lighting fixture shall be provided in every habitable room, bathroom, hallway, stairway, attached garage, and detached garage with electrical power, in utility rooms and basements where such spaces are used for storage or contain equipment requiring service, and to illuminate outdoor entrances and exits.

(5) *Ground fault circuit interrupters.* Ground fault circuit interrupter protection shall be provided for all receptacles in bathrooms, above kitchen counters, attached and detached garages provided with power, at readily accessible receptacles within 6 feet of sinks, unfinished basements, and at outdoor locations. The exceptions of the *National Electrical Code* 210.8(A) 3 and 5 shall apply.

(6) *Laundries.* Each laundry shall be provided with at least one separate 20-ampere circuit.

(7) *Heat sources.* Any heat source shall be provided with a separate circuit.

(8) *Exposed wiring methods.* All exposed wiring methods shall be installed in accordance with the applicable *National Electrical Code* article.

**408.1 Materials.** Plumbing materials and supplies shall not be used for repairs that are prohibited in the Uniform Plumbing Code.

**702.6 Materials and methods.** New work shall comply with the materials and methods requirements in the International Building Code, International Residential Code, International Energy Conservation Code, International Mechanical Code, International Fuel Gas Code, NFPA70, and Uniform Plumbing Code, as applicable, that specify material standards, detail of installation and connection, joints, penetrations, and continuity of any element, component, or system in the building.

**702.6.2 International Mechanical Code.** The following sections of the International Mechanical Code shall constitute the mechanical materials and methods requirements for Level 1 alterations:

1. All of Chapter 3, entitled "General Regulations," except Sections 303.7 and 306.
2. All of Chapter 8, entitled "Chimneys and Vents."
3. All of Chapter 9, entitled "Specific Appliances."

**702.6.3 International Residential Code.** The following sections of Part V—Mechanical of the International Residential Code shall constitute the residential mechanical and fuel gas materials and methods requirements for Level 1 alterations:

1. All of Chapter 13, entitled "General Mechanical System Requirements," except Section M1305.
2. All of Chapter 18, entitled "Chimneys and Vents."
3. All of Sections G2431 through G2454 governing the appliances and equipment specifically identified therein.

**805.3.1.2.1 Fire escape access and details.** Fire escapes shall comply with all of the following requirements:

1. Occupants shall have unobstructed access to the fire escape without having to pass through a room subject to locking.

2. Access to a new fire escape shall be through a door, except that windows shall be permitted to provide access from single-dwelling units or sleeping units in Group R-1, R-2 and I-1 occupancies or to provide access from spaces having a maximum occupant load of 10 in other occupancy classifications.
  - 2.1. The window shall have a minimum net clear opening of 5 square feet (0.46 m<sup>2</sup>).
  - 2.2. The minimum net clear opening height shall be 24 inches (610 mm) and net clear opening width shall be 20 inches (508 mm).
  - 2.3. The bottom of the clear opening shall not be greater than 48 inches (1220 mm) above the floor.
  - 2.4. The operation of the window shall comply with the operational constraints of the International Building Code.
3. Newly constructed fire escapes shall be permitted only where exterior stairs cannot be utilized because of lot lines limiting the stairway size or because of the sidewalks, alleys, or roads at grade level.
4. Openings within 10 feet (3048 mm) of fire escape stairways shall be protected by fire assemblies having minimum 3/4-hour fire-resistance ratings.

**Exception:** Opening protection shall not be required in buildings equipped throughout with an approved automatic sprinkler system.

5. In all buildings of Group E occupancy, up to and including the 12th grade, buildings of Group I occupancy, rooming houses and childcare centers, ladders of any type are prohibited on fire escapes used as a required means of egress.

**810.1 Minimum fixtures.** Where the occupant load of the story is increased by more than 20 percent, plumbing fixtures for the story shall be provided in quantities specified in Chapter 29, Plumbing Systems of the International Building Code based on the increased occupant load.

**1009.1 Increased demand.** Where the occupancy of an existing building or part of an existing building is changed such that the new occupancy is subject to increased or different plumbing fixture requirements or to increased water supply requirements in accordance with the Uniform Plumbing Code, the new occupancy shall comply with the intent of the respective Uniform Plumbing Code provisions.

**1010.2 Food-handling occupancies.** If the new occupancy is a food-handling establishment, all existing sanitary waste lines above the food or drink preparation or storage areas shall be panned or otherwise protected to prevent leaking pipes or condensation on pipes from contaminating food or drink. New drainage lines shall not be installed above such areas and shall be protected

in accordance with the Uniform Plumbing Code.

**1010.3 Interceptor required.** If the new occupancy will product grease or oil-laden wastes interceptors shall be provided as required in the Uniform Plumbing Code.

**1010.5 Group I-2.** If the occupancy group is changed to Group I-2, the plumbing system shall comply with the applicable requirements of the Uniform Plumbing Code.

**1011.4.1 Means of egress for change to higher hazard category.** Where a change of occupancy classification is made to a higher hazard category (lower number) as shown in Table 1011.4, the means of egress shall comply with the requirements of Chapter 10 of the International Building Code.

**Exceptions:**

1. Stairways shall be enclosed in compliance with the applicable provisions of Section 903.1.
2. Existing stairways including handrails and guards complying with the requirements of Chapter 9 shall be permitted for continued use subject to approval of the building official.
3. Any stairway replacing an existing stairway within a space where the pitch or slope cannot be reduced because of existing construction shall not be required to comply with the maximum riser height and minimum tread depth requirements.
4. Existing corridor walls constructed on both sides of wood lath and plaster in good condition or 1/2- inch-thick (12.7 mm) gypsum wallboard shall be permitted. Such walls shall either terminate at the underside of a ceiling of equivalent construction or extend to the underside of the floor or roof next above.
5. Existing corridor doorways, transoms, and other corridor openings shall comply with the requirements in Sections 805.5.1, 805.5.2 and 805.5.3.
6. Existing dead-end corridors shall comply with the requirements in Section 805.6.
7. An existing operable window with clear opening area no less than 4 square feet (0.38 m<sup>2</sup>) and minimum opening height and width of 22 inches (559 mm) and 20 inches (508 mm), respectively, provided the operable window has a sill height of not more than 48 inches (1,220 mm) above the floor, shall be accepted as an emergency escape and rescue opening.

**1011.6.2 Exterior wall rating for change of occupancy classification to an equal or lesser hazard category.** When a change of occupancy classification is made to an equal or lesser hazard category as shown in Table 1011.6, existing exterior walls, including openings, shall be accepted.

Exception. Where a property line is platted creating a Group R-3, multifamily dwelling (town house), the walls separating the dwelling units shall be constructed to provide a continuous fire separation using construction materials consistent with the existing wall or complying with the requirements for a new structure. The fire-resistive elements are not required to be continuous between concealed floor spaces, although there shall be provided a draft stop, located above and in line with the dwelling unit separation walls.

**SECTION 1106**

**STORM SHELTERS: Not adopted by the city.**

ADOPTED this 4<sup>th</sup> day of June, 2019.

---

Jeremy Menning  
MAYOR

(Seal)

ATTEST:

---

Karen Wilber  
Municipal Finance Officer

FIRST READING AND HEARING – May 21, 2019  
SECOND READING AND ADOPTION – June 4, 2019  
PUBLICATION – June 13, 2019  
EFFECTIVE DATE – July 3, 2019

